



PO Box 45746
 Atlanta, GA 30320
 P 877-697-5646
 www.rooflogos.com

LogoBondAM Asphalt Primer is a water based product developed to help ensure superior finished coating adhesion as well as prevent coating discoloration. For metal roofing, it is recommended that all asphalt products be removed. **LogoBondAM** is to be applied and allowed to dry over those areas where residual asphalt remains. Primer application can be by brush, roller or airless sprayer. Also designed for use over smooth and granulated modified bitumen roof systems as required.

BENEFITS: Promotes coating adhesion, prevents asphalt bleed-through, water based, easy application, environmentally friendly.

COVERAGE: 1 gallon per 200 square feet.

DRYING TIME: 2 - 4 hours dependant on temperature and humidity.

STORAGE: In a clean, warm and well-ventilated area. Storage area temperature must be above 45°F.

PRECAUTIONS: **DO NOT APPLY IF TEMPERATURE IS BELOW 55° F or above 110°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 48-72 HOURS.** Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur. **DO NOT ALLOW PRODUCT TO FREEZE.** Do not heat container or store at temperatures greater than 120°F.

CLEANUP: Clean tools with mineral spirits or paint thinner, if primer has dried. If primer is still wet, clean up with warm soapy water.

CAUTION!

KEEP OUT OF REACH OF CHILDREN. Close container after each use.

DO NOT TAKE INTERNALLY!

If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!

MAXIMUM V.O.C = 99 G/L

PHYSICAL PROPERTIES

Liquid Appearance.....White
 Dry Appearance.....Clear Sheen
 Percent Solids, Weight.....25%
 Application.....Brush, Roller, Airless Sprayer
 Viscosity (stomer).....80-90 KU